Department of Property & Procurement

Government of the United States Virgin Islands

3274 ESTATE RICHMOND, CHRISTIANSTED, U. S. VIRGIN ISLANDS 00820 8201 SUB BASE, SUITE 4, ST. THOMAS, U. S. VIRGIN ISLANDS 00802 ST. CROIX MAIN OFFICE: 340.773.1561 ST. THOMAS MAIN OFFICE: 340.774.0828 ST. CROIX FAX: 340.773.0986 ST. THOMAS FAX: 340.777.9587



HTTP://DPP.VI.GOV

AMENDMENT ONE (1)

March 15, 2018	
TO:	
SUBJECT:	IFB014DPWC18 (C) VITRAN Maintenance & Operations Facility in Estate Anna's Hope, St. Croix.
INSERT:	Questions & Answers

QUESTION: Is the asphalt thickness of 1" and ½" for exterior Driveway and parking lot surfaces adequate where transit buses And heavy equipment will easily wear on the surface integrity Over a short period of time?

ANSWER: Concrete pavement thickness – Concrete pavement For vehicles where indicated shall be the same throughout the Project, which is indicated on Sheet S1 as: 6", 4000 psi concrete With 6"x 6"x W2.1x W2.1WWF on 10ml vapor barrier

Asphalt thickness – The bidder's reference to 1" and ½" Dimensions were the maximum size of aggregate not the course Thickness. The course thicknesses are specified as: Base Course 2½" Surface Course 1½"

All other terms and conditions remain the same.

A copy of this amendment must be returned with your bid.